

# Retrieving a recommendation configuration (Graniitti API)

Learn how to retrieve one or all [recommendation configurations](#) with the Graniitti API.

- [Retrieving a single recommendation configuration for a site](#)
- [Retrieving all recommendation configurations for a site](#)

## Retrieving a single recommendation configuration for a site

To retrieve a single recommendation configuration for a site, make a [Graniitti API GET request](#) to `/sites/<site_id>/recommendations/<recommendation_id>`, where `<recommendation_id>` is the ID of the recommendation configuration.

```
curl -X GET \  
--header 'Authorization: Bearer <access_token>' \  
'https://<graniitti_api_base_url>/sites/<site_id>/recommendations/<recommendation_id>'
```

If the request is successful, the API returns a JSON object containing the requested recommendation configuration. For more information about the object, see the [recommendation configuration reference](#).

## Retrieving all recommendation configurations for a site

To retrieve all recommendation configurations for a site, make a [Graniitti API GET request](#) to `/sites/<site_id>/recommendations`.

```
curl -X GET \  
--header 'Authorization: Bearer <access_token>' \  
'https://<graniitti_api_base_url>/sites/<site_id>/recommendations'
```

If the request is successful, the API returns a JSON array of objects containing all recommendation configurations for the site. Each object contains a single recommendation configuration. For more information about the object, see the [recommendation configuration reference](#).